


Transport, handling and storage of Trespa[®] panels

This document is intended to provide general recommendations only. Trespa provides these guidelines and all testing, code and design data for informational purposes only and strongly advises that the customer, project owner and architect seek independent advice from a certified construction professional and/or engineer regarding application and installation as well as compliance with design requirements, applicable codes, laws and regulations, and test standards. Please check your local codes and applicable design requirements for proper use.

General

Handling and moving panels should only be undertaken by trained personnel using the correct equipment. Trespa® panels are decorative high-pressure compact laminates consisting of layers of wood-based fibres, impregnated with thermosetting resins. Panels should be handled with care to prevent damage to the decorative surface. Furthermore, treat the panels similar to treating hardwood.



Transport

- Use a proper forklift with a load capacity of at least 2500 kg (≈ 5512 lbs) and forks with a minimum length of 1.5 meters (≈ 59 in).
- Secure the panels with steel straps during transit.
- Fit protective corner sections under the straps.

Handling

- Treat panels with care.
- Do not slide panels. Lift panels when moving.
- Prevent dirt on and between the panels.
- Use adhesive stickers for marking / coding and remove immediately after installation.

Storage

- Store panels in a dry, clean, frost-free room.
- Maximum stack height = 6 m (≈ 20 ft).
- Place pallets and panels on a level surface which

provides full support.

- Keep panels in the original packaging.
- Remove steel straps if the panels are to be stored for a long time.
- Prevent a film of moisture from forming between the panels.
- Do not place any moisture-sensitive (paper) layers between the panels.
- Prevent unbalanced (one side only) moisture or temperature exposure by:
 - Removing any protective foil within 24 hours when panels are no longer stacked as a package.
 - Leaving panels lying flat on top of each other.
 - Avoiding cavities between the panels e.g. due to panels having been machined.

Please check www.trespa.info for more technical details or contact your local Trespa representative.

DISCLAIMER

This is a print generated by you from www.trespa.info ("Website"). By accessing the Website and printing this document you have accepted the Terms of Use of the Website. Please refer to the Website for all conditions that apply to this document. The system shown in this document may not be suitable for all applications and jurisdictions. We provide you with testing data and certification information for informational purposes only. We strongly recommend that you or any other user of this document obtains advice regarding compliance with design requirements, applicable codes, laws and regulations, and test standards from independent experts. Please check your local codes and design requirements for proper use. Trespa will not accept any liability in relation to your use of this document.

All intellectual property rights, including copyrights and other rights regarding the content of the Website and this print generated from the Website (including logos, trademarks, service marks, software, databases, audio, video, text and photographs) are owned by Trespa and/or its licensors. ® Trespa, Meteon, Pura, Pura NFC, Athlon, Izeon, TopLab, TopLab^{PLUS}, TopLab^{PLUS ALIGN}, TopLab^{ECO-FIBRE}, TopLab^{VERTICAL}, TopLab^{BASE}, Trespa Essentials and Mystic Metallics, Virtuon, Volkern are registered trademarks of Trespa.

All oral and written statements, offers, quotations, sales, supplies, deliveries and/or agreements and all related activities of Trespa are governed by the Trespa General Terms and Conditions of Sale (Algemene verkoopvoorwaarden Trespa International B.V.) filed with the Chamber of Commerce (NL) on 9 May 2023 under number 24270677, which can be found on and downloaded from the Trespa website, www.trespa.com.

All oral and written statements, offers, quotations, sales, supplies, deliveries and/or agreements and all related work of Trespa North America, Ltd. are governed by the Trespa North America General Terms and Conditions of Sale, which can be found on and downloaded from the Trespa website, www.trespa.com/documentation. A copy of these general conditions of sale will be provided free of charge on request. All general terms and conditions other than the conditions mentioned above are dismissed and do not apply, regardless of whether such terms and conditions are referred to on requests for offers, offer confirmations, stationery and/or other documents of the other party, even if Trespa does not expressly object to such terms and conditions.